

品牌	轴承	电压	频率	功率	转速	风量		静压		燥音
型号	B/S	V	HZ	W	RPM	m3/min	CFM	mm-H2O	In-H2O	dba
SP06025L	B/S	220	50/60	2	3000	0.39	13.8	2.3	0.09	24
SP06025M	B/S	220	50/60	3	4000	0.51	18.3	4.2	0.16	30
SP06025H	B/S	220	50/60	4	5500	0.71	25.2	6.5	0.25	37
SP06030_2H	B/S	220	50/60	5	2500	0.22	7.9	1.6	0.06	26
SP07025L	B/S	220	50/60	2	2500	0.55	19.7	1.9	0.07	24
SP07025M	B/S	220	50/60	3	3000	0.67	23.7	3.1	0.12	28
SP07025H	B/S	220	50/60	4	3500	0.78	27.6	3.8	0.15	33
SP08025_2H	B/S	220	50/60	13/11	2500/3000	0.62/0.71	22/25	4.5/5.3	0.18/0.21	28/29
SP08038_2H	B/S	220	50/60	13/10	2450/2950	0.74/0.88	26/31	4.3/6.0	0.17/0.24	29/30
SP09225_2H	B/S	220	50/60	15/13	2400/2800	0.85/0.99	30/35	4.0/5.0	0.16/0.20	30/31
SP09238_2H	B/S	220	50/60	9/12	2200/2400	1.27/1.55	45/55	4.0/5.0	0.16/0.20	37/41
SP11025_2H	B/S	220	50/60	19/18	2200/2500	1.80/2.30	64/81	5.0/5.9	0.20/0.23	37/38
SP12025_2H	B/S	220	50/60	19/18	2200/2500	1.80/2.30	64/81	5.0/5.9	0.20/0.23	37/38
SP12038_2L	B/S	220	50/60	11/15	2150/2300	2.21/2.04	72/78	3.30/2.29	0.09/0.13	26/27
SP12038_2M	B/S	220	50/60	11/15	2400/2600	2.40/2.37	79/85	3.56/5.33	0.14/0.21	36/37
SP12038_2H	B/S	220	50/60	21/19	2600/3000	2.57/2.97	91/105	6.35/7.62	0.25/0.30	43/44
SP13538_2H	B/S	220	50/60	25/20	2250/2400	2.69/3.11	95/110	7.2/8.1	0.28/0.32	44/50
SP15050_2H	B/S	220	50/60	35/32	2700/3000	5.09/5.66	180/200	9.6/12.2	0.38/0.48	50/52
SP15055_2H	B	220	50/60	35/32	2700/3000	5.09/5.66	180/200	9.6/12.2	0.38/0.48	50/52
SP17238_2H	B	220	50/60	35/32	2850/3200	5.21/6.17	184/218	15.7/15.7	0.62/0.86	49/52
SP17251_2H	B/S	220	50/60	35/32	2700/3000	5.09/5.66	180/200	9.6/12.2	0.38/0.48	50/52
SP18060_2H	B	220	50/60	60/75	2650/3000	10.76/12.74	380/450	20/26	0.79/1.02	60
SP20060_2H	B	220	50/60	60/75	2650/3000	10.76/12.74	380/450	20/26	0.79/1.02	60
SP22060_2H	B	220	50/60	60/75	2650/3000	10.70/12.70	380/450	20/26	0.79/1.02	60
SP22580_2H	B	220	50/60	65	2550/2800	19.8/23.2	486/534	19.8/23	1.09/1.28	58/61
SP25489_2H	B	220	50/60	60/67	2150/2000	24.5/22.8	700/630	7.9/8.7	0.31/0.35	56
SP25489_2H	B	220	50/60	60/67	1400/1600	24.5/22.8	700/630	7.9/8.7	0.31/0.35	56
SP28080_2H	B	220	50/60	112/148	2550/2800	30.9/32.0	1090/1130	20.0/26	0.78/1.02	68/70