

□ 200

Axial fan

× 200 × 60mm



General Specifications

- Motor : Singal phase induction capacitor motor
- Frame & Impller :Al Die-casting & PBT plsatic
- Storage temperature : -40°C to +75°C
- Operating temperature : -10°C to +60°C

Major Characteristic Parameters

| 品牌 | 轴承 | 电压 | 频率 | 功率 | 转速 | 风量 | | 静压 | | 噪音 |
|----------------|-------|-----|-------|-------|-----------|-------------|---------|--------|-----------|------|
| 型号 | B/S | V | HZ | W | RPM | m3/mi n | CFM | mm-H2O | In-H2O | dba |
| SP200B11H-60AL | B / S | 110 | 50/60 | 60/75 | 2650/3000 | 10.76/12.74 | 380/450 | 20/26 | 0.79/1.02 | 60.0 |
| SP200B22H-60AL | B / S | 220 | 50/60 | 60/75 | 2650/3000 | 10.76/12.74 | 380/450 | 20/26 | 0.79/1.02 | 60.0 |
| SP200B11H-60AT | B / S | 110 | 50/60 | 60/75 | 2650/3000 | 10.76/12.74 | 380/450 | 20/26 | 0.79/1.02 | 60.0 |
| SP200B22H-60AT | B / S | 220 | 50/60 | 60/75 | 2650/3000 | 10.76/12.74 | 380/450 | 20/26 | 0.79/1.02 | 60.0 |

*Bearing system B: Two Ball Bearing S: Sleeve Bearing

