

尺寸	轴承	电压	启动电压	电流	功率	转速	风量	静压	噪音		
规格	B/S	V	V	A	W	RPM	m ³ /min	CFM	mm-H ₂ O	In-H ₂ O	dba
60×60×25mm	B/S	48	28.0~56.0	0.05~0.12	2.40~5.76	3100~6800	0.40~0.99	14.10~34.80	2.50~13.00	0.10~0.51	26.0~46.5
60×60×38mm	B/S	48	28.0~56.0	0.18~0.25	8.64~12.00	8000~12000	1.22~1.90	43.10~67.30	22.90~52.60	0.90~2.07	51.0~61.8
70×70×25mm	B/S	48	28.0~56.0	0.04~0.07	1.92~3.36	3000~5500	0.85~1.55	30.00~54.80	3.90~12.80	0.15~0.50	27.0~45.0
80×80×25mm	B/S	48	28.0~56.0	0.30~0.40	14.40~19.20	5000~6000	1.72~2.07	60.80~73.00	10.30~14.80	0.40~0.58	46.0~51.0
80×80×38mm	B/S	48	28.0~56.0	0.14~0.90	6.72~43.20	4200~9000	1.65~3.68	58.20~130.00	10.40~50.90	0.41~2.00	45.0~65.5
92×92×25mm	B/S	48	28.0~56.0	0.05~0.12	2.40~5.76	2100~4200	1.11~2.29	39.20~81.0	2.20~9.20	0.09~0.40	25.0~49.0
92×92×38mm	B/S	48	28.0~56.0	0.25~0.60	12.00~28.80	4400~8000	2.66~4.95	94.11~174.98	14.58~46.03	0.57~1.81	51.2~66.5
120×120×25mm	B/S	48	28.0~56.0	0.13~0.30	6.24~14.40	2500~3400	2.60~3.54	91.90~125.10	5.50~10.20	0.22~0.40	37.0~45.0
120×120×38mm	B/S	48	28.0~56.0	0.09~0.30	4.32~14.40	2600~4200	3.25~5.05	114.70~178.40	10.40~23.80	0.41~0.94	41.0~54.0
140×140×25mm	B/S	48	28.0~56.0	0.06~0.19	2.88~9.12	1200~2000	1.78~2.78	63.0~98.4	1.20~2.80	0.05~0.11	25.0~38.0
150×150×50mm	B/S	48	28.0~56.0	0.90~1.50	43.20~72.00	3500~4400	7.79~7.79	275~332	22.5~34.2	0.89~1.35	57.0~63.5
172×150×51mm	B/S	48	28.0~56.0	0.90~1.50	43.20~72.00	3500~4400	7.79~7.79	275~332	22.5~34.2	0.89~1.35	57.0~63.5
200×200×60mm	B	48	28.0~56.0	0.40~1.10	19.20~52.80	2000~2800	12.04~16.86	425~595	46.40~65.00	1.82~2.55	46.5~74.4
224×89mm	B	48	28.0~56.0	1.20	57.60	2950	17.60	618	21.20	0.83	60.0
280×280×89mm	B	48	28.0~56.0	57.60	124.80	2750	32.00	1130	22.44	0.88	70.0