

□ 172 cooling fan ×150×50mm



General Specifications

- Motor : 4 Poles brushless DC motor
- Frame & Impeller: Al die-casting & Plastic
- Storage temperature : -40° to +75°
- Operating temperature : -10° to +70°

Major Characteristic Parameters

品牌	轴承	电压	启动电压	电流	功率	转速	风量	静压	噪音		
型号	B/S	V	V	A	W	RPM	m3/min	CFM	mm-H2O	In-H2O	dba
SP172B24M-50DL	B / S	24	14.0~26.4	1.50	36.00	3500	7.79	275	22.5	0.89	57.0
SP172B48M-50DL	B / S	48	28.0~56.0	0.90	43.20	3500	7.79	275	22.5	0.89	57.0
SP172B24H-50DL	B / S	24	14.0~26.4	2.10	50.40	4000	8.69	307	28.0	1.10	61.5
SP172B48H-50DL	B / S	48	28.0~56.0	1.20	57.60	4000	8.69	307	28.0	1.10	61.5
SP172B24U-50DL	B / S	24	14.0~26.4	2.88	69.12	4400	9.40	332	34.2	1.35	63.5
SP172B48U-50DL	B / S	48	28.0~56.0	1.50	72.00	4400	9.40	332	34.2	1.35	63.5

*Bearing system B: Two Ball Bearing S: Sleeve Bearing

