

30 cooling fan × 30 × 10mm



General Specifications

- Motor : 6 Poles brushless DC motor
- Frame & Impeller: Plastic (UL 94V-0)
- Storage temperature : -40° to +75°
- Operating temperature : -10° to +70°

Major Characteristic Parameters

品牌	轴承	电压	启动电压	电流	功率	转速	风量	静压	噪音		
型号	B/S	V	V	A	W	RPM	m ³ /min	CFM	mm-H ₂ O	In-H ₂ O	dba
SP30B05L-10DL	B / S	5	4.5~5.5	0.10	0.50	5800	0.07	2.56	2.59	0.10	21.5
SP30B12L-10DL	B / S	12	7.0~13.2	0.03	0.36	5800	0.07	2.56	2.59	0.10	21.5
SP30B05M-10DL	B / S	5	4.5~5.5	0.15	0.75	8500	0.11	3.46	3.76	0.14	26.5
SP30B12M-10DL	B / S	12	7.0~13.2	0.05	0.60	8500	0.11	3.46	3.76	0.14	26.5
SP30B05H-10DL	B / S	5	4.5~5.5	0.17	0.85	10500	0.12	4.30	4.48	0.17	29.2
SP30B12H-10DL	B / S	12	7.0~13.2	0.08	0.96	10500	0.12	4.30	4.48	0.17	29.2
SP30B05U-10DL	B / S	5	4.5~5.5	0.22	1.10	13000	0.16	5.56	5.89	0.23	33.5
SP30B12U-10DL	B / S	12	7.0~13.2	0.09	1.08	13000	0.16	5.56	5.89	0.23	33.5

*Bearing system B: Two Ball Bearing S: Sleeve Bearing

