

40 cooling fan ×40×20mm



General Specifications

- Motor : 6 Poles brushless DC motor
- Frame & Impeller: Plastic (UL 94V-0)
- Storage temperature : -40° to +75°
- Operating temperature : -10° to +70°

Major Characteristic Parameters

品牌	轴承	电压	启动电压	电流	功率	转速	风量	静压	噪音		
型号	B/S	V	V	A	W	RPM	m3/min	CFM	mm-H ₂ O	In-H ₂ O	dba
SP40B12L-20DL	B / S	12	7.0~13.2	0.10	1.20	5000	0.21	7.4	4.8	0.19	21.0
SP40B24L-20DL	B / S	24	14.0~24.6	0.07	1.68	5000	0.21	7.4	4.8	0.19	21.0
SP40B12M-20DL	B / S	12	7.0~13.2	0.12	1.44	6500	0.22	9.6	8.1	0.32	24.5
SP40B24M-20DL	B / S	24	14.0~24.6	0.09	2.16	6500	0.22	9.6	8.1	0.32	24.5
SP40B12H-20DL	B / S	12	7.0~13.2	0.16	1.92	8600	0.31	11.1	10.8	0.43	32.5
SP40B24H-20DL	B / S	24	14.0~24.6	0.13	3.12	8600	0.31	11.1	10.8	0.43	32.5
SP40B12U-20DL	B / S	12	7.0~13.2	0.22	2.64	9500	0.31	11.6	11.9	0.47	33.5

*Bearing system B: Two Ball Bearing S: Sleeve Bearing

