

## 45 cooling fan ×45×10mm



### General Specifications

- Motor : 6 Poles brushless DC motor
- Frame & Impeller: Plastic (UL 94V-0)
- Storage temperature : -40° to +75°
- Operating temperature : -10° to +70°

### Major Characteristic Parameters

品牌	轴承	电压	启动电压	电流	功率	转速	风量	静压	噪音		
型号	B/S	V	V	A	W	RPM	m3/min	CFM	mm-H2O	In-H2O	dba
SP45B05L-10DL	B / S	5	4.5~5.5	0.14	0.70	5000	0.31	10.64	3.22	0.13	30.2
SP45B12L-10DL	B / S	12	7.0~13.2	0.07	0.84	5000	0.31	10.64	3.22	0.13	30.2
SP45B05M-10DL	B / S	5	4.5~5.5	0.18	0.90	6000	0.36	12.53	4.67	0.18	32.6
SP45B12M-10DL	B / S	12	7.0~13.2	0.08	0.96	6000	0.36	12.53	4.67	0.18	32.6
SP45B05H-10DL	B / S	5	4.5~5.5	0.27	1.35	6500	0.39	13.81	5.12	0.22	36.5
SP45B12H-10DL	B / S	12	7.0~13.2	0.10	1.20	6500	0.39	13.81	5.12	0.22	36.5
SP45B05U-10DL	B / S	5	4.5~5.5	0.15	0.75	7000	0.41	14.15	5.51	0.24	38.4
SP45B12U-10DL	B / S	12	7.0~13.2	0.08	0.96	7000	0.41	14.15	5.51	0.24	38.4

\* Bearing system B: Two Ball Bearing S: Sleeve Bearing

