

60 cooling fan ×60×20mm



General Specifications

- Motor : 6 Poles brushless DC motor
- Frame & Impeller: Plastic (UL 94V-0)
- Storage temperature : -40° to +75°
- Operating temperature : -10° to +70°

Major Characteristic Parameters

品牌	轴承	电压	启动电压	电流	功率	转速	风量	静压	噪音		
型号	B/S	V	V	A	W	RPM	m ³ /min	CFM	mm-H ₂ O	In-H ₂ O	dba
SP60B12L-20DL	B / S	12	7.0~13.2	0.07	0.84	3200	0.38	13.50	3.00	0.12	24.0
SP60B24L-20DL	B / S	24	14.0~26.4	0.04	0.96	3200	0.38	13.50	3.00	0.12	24.0
SP60B12M-20DL	B / S	12	7.0~13.2	0.09	1.08	3600	0.42	14.80	3.80	0.15	26.0
SP60B24M-20DL	B / S	24	14.0~26.4	0.05	1.20	3600	0.42	14.80	3.80	0.15	26.0
SP60B12H-20DL	B / S	12	7.0~13.2	0.11	1.32	4000	0.46	16.40	4.80	0.19	29.0
SP60B24H-20DL	B / S	24	14.0~26.4	0.05	1.20	4000	0.46	16.40	4.80	0.19	29.0
SP60B12U-20DL	B / S	12	7.0~13.2	0.13	1.56	4400	0.51	18.10	5.80	0.23	31.0
SP60B24U-20DL	B / S	24	14.0~26.4	0.07	1.68	4400	0.51	18.10	5.80	0.23	31.0
SP60B12HU-20DL	B / S	12	7.0~13.2	0.17	2.04	4800	0.56	19.60	6.90	0.27	33.0
SP60B24HU-20DL	B / S	24	14.0~26.4	0.09	2.16	4800	0.56	19.60	6.90	0.27	33.0

*Bearing system B: Two Ball Bearing S: Sleeve Bearing

