

规格	轴承	电压	启动电压	电流	功率	转速	风量		静压		噪音
型号	B/S	V	V	A	W	RPM	m <sup>3</sup> /mi n	CFM	mm-H2O	In-H2O	dba
30×30×10mm	B	12	7.0~13.2	0.04~0.06	0.48~0.72	5500~8500	0.030~0.047	1.06~1.66	3.66~9.40	0.144~0.370	24.0~31.0
35×35×10mm	B	12	7.0~13.2	0.04~0.08	0.48~0.96	5500~8500	0.038~0.060	1.34~2.12	4.14~11.25	0.163~0.443	24.0~31.0
40×40×10mm	S/B	12	7.0~13.2	0.04~0.08	0.48~0.96	5500~8500	0.055~0.085	1.94~3.00	5.37~14.33	0.21~0.56	28.0~34.5
40×40×20mm	S/B	12	7.0~13.2	0.07~0.15	0.84~1.80	3000~6000	0.08~0.11	2.20~3.50	2.20~8.50	0.19~0.33	21.4~29.6
50×50×15mm	S/B	12	7.0~13.2	0.20~0.35	2.40~4.20	3500~6500	0.067~0.130	2.35~4.60	7.00~22.0	0.26~0.87	27.0~45.3
50×50×20mm	S/B	12	7.0~13.2	0.12~0.16	1.44~2.76	3700~5300	0.13~0.19	4.45~6.75	7.85~18.60	0.31~0.73	28.0~38.5
60×60×15mm	S/B	12	7.0~13.2	0.13~0.25	1.56~3.00	3500~4600	0.10~0.13	3.55~4.45	10.80~15.53	0.45~0.61	27.0~35.0
60×60×25mm	S/B	12	7.0~13.2	0.18~0.24	2.16~2.88	3200~3700	0.19~0.22	6.71~7.88	10.86~15.49	0.43~0.61	34.0~39.0
75×70×15mm	S/B	12	7.0~13.2	0.11~0.35	1.32~4.20	2500~3500	1.05~0.13	3.72~4.67	10.58~15.09	0.41~0.59	27.0~35.0
75×70×25mm	S/B	12	7.0~13.2	0.10~0.34	1.20~4.08	2800~4400	0.26~0.43	9.26~15.33	7.26~24.82	0.29~0.98	39.0~51.0
75×75×30mm	S/B	12	7.0~13.2	0.09~0.45	1.08~5.40	2600~4600	0.31~0.89	10.90~22.50	7.80~20.20	0.31~0.80	32.1~53.0
97×94×33mm	S/B	12	7.0~13.2	0.38~1.90	4.56~22.80	2700~5000	0.69~1.29	24.20~45.57	18.93~73.64	0.75~2.90	48.0~62.5
120×120×32mm	S/B	12	7.0~13.2	0.38~1.90	4.56~22.80	2100~3200	0.69~1.29	24.20~45.57	18.93~73.64	0.745~2.90	48.0~62.5
145×140×40mm	B	12	7.0~13.2	1.30~1.75	15.60~21.00	2200~2800	1.50~1.83	53.8~65.0	14.70~33.00	0.57~1.30	35.0~42.0

注：如果以上没有您要的规格及参数，请与我们销售代表联系并索取。谢谢！