

规格	轴承	电压	启动电压	电流	功率	转速	风量		静压		噪音
型号	B/S	V	V	A	W	RPM	m ³ /mi n	CFM	mm-H2O	In-H2O	dba
50×50×15mm	S/B	24	14.0~26.4	0.20~0.30	4.80~7.20	3500~6500	0.067~0.130	2.35~4.60	7.00~22.0	0.26~0.87	27.0~45.3
60×60×15mm	S/B	24	14.0~26.4	0.07~0.10	1.68~2.40	3500~4600	0.10~0.13	3.55~4.45	10.80~15.53	0.45~0.61	27.0~35.0
75×70×15mm	S/B	24	14.0~26.4	0.06~0.30	1.44~7.20	2500~3500	1.05~0.13	3.72~4.67	10.58~15.09	0.41~0.59	27.0~35.0
75×75×30mm	S/B	24	14.0~26.4	0.04~0.40	0.96~9.60	2600~4600	0.31~0.89	10.90~22.50	7.80~20.20	0.31~0.80	32.1~53.0
97×94×33mm	S/B	24	14.0~26.4	0.19~0.78	4.56~18.60	2700~5000	0.69~1.29	24.20~45.57	18.93~73.64	0.75~2.90	48.0~62.5
120×120×32mm	S/B	24	14.0~26.4	0.20~0.95	4.80~22.80	2100~3200	0.69~1.29	24.20~45.57	18.93~73.64	0.745~2.90	48.0~62.5
145×140×40mm	B	24	14.0~26.4	0.65~1.15	15.60~27.60	2200~2800	1.50~1.83	53.8~65.0	14.70~33.00	0.57~1.30	35.0~42.0

注：如果以上没有您要的规格及参数，请与我们联系并索取。谢谢！