

规格	轴承	电压	启动电压	电流	功率	转速	风量		静压		噪音
型号	B/S	V	V	A	W	RPM	m ³ /mi n	CFM	mm-H ₂ O	In-H ₂ O	dba
30×30×10mm	B	5	4.5~5.5	0.06~0.15	0.30~0.75	5500~8500	0.030~0.047	1.06~1.66	3.66~9.40	0.144~0.370	24.0~31.0
35×35×10mm	B	5	4.5~5.5	0.05~0.15	0.25~0.96	5500~8500	0.038~0.060	1.34~2.12	4.14~11.25	0.163~0.443	24.0~31.0
40×40×10mm	S/B	5	4.5~5.5	0.06~0.16	0.30~0.80	5500~8500	0.055~0.085	1.94~3.00	5.37~14.33	0.21~0.56	28.0~34.5
40×40×20mm	S/B	5	4.5~5.5	0.14~0.26	0.70~1.30	3000~6000	0.06~0.09	2.20~3.50	2.20~3.50	3.00~6.80	21.4~29.6
50×50×15mm	S/B	5	4.5~5.5	0.28~0.39	1.40~1.95	3500~5500	0.067~0.107	2.35~3.77	7.00~18.10	0.26~0.71	27.0~37.2
50×50×20mm	S/B	5	4.5~5.5	0.24~0.32	1.20~1.60	3700~4900	0.13~0.17	4.45~5.83	7.85~16.15	0.31~0.64	28.0~36.5
60×60×15mm	S/B	5	4.5~5.5	0.16~0.20	0.80~1.00	3500~4000	0.10~0.11	3.55~3.85	10.80~11.50	0.45~0.45	27.0~31.0
60×60×25mm	S/B	5	4.5~5.5	0.36~0.48	1.80~2.40	3200~3700	0.19~0.22	6.71~7.88	10.86~15.49	0.43~0.61	34.0~39.0
75×70×15mm	S/B	5	4.5~5.5	0.16~0.24	0.80~1.20	2500~3000	1.05~0.11	3.72~4.04	10.58~12.07	0.41~0.47	27.0~31.0
75×70×25mm	S/B	5	4.5~5.5	0.20~0.32	1.00~1.60	2800~3400	0.26~0.32	9.26~11.31	7.26~12.14	0.29~0.48	39.0~43.0

注：如果以上没有您要的规格及参数，请与我们联系并索取。谢谢！