

## □ 143 DC Blower

×136×40mm



### General Specifications

- Motor : 6 Poles brushless DC motor
- Frame & Impeller: Plastic (UL 94V-0)
- Storage temperature : -40° to +75°
- Operating temperature : -10° to +70°

### Major Characteristic Parameters

品牌	轴承	电压	启动电压	电流	功率	转速	风量	静压	噪音		
型号	B/S	V	V	A	W	RPM	m3/min	CFM	mm-H2O	In-H2O	dba
SP143B12L-42DL	B	12	7.0~13.2	1.30	15.60	2200	1.50	53.8	14.7	0.57	35.0
SP143B24L-42DL	B	24	14.0~26.4	0.65	15.60	2200	1.50	53.8	14.7	0.57	35.0
SP143B48L-42DL	B	48	28.0~56.0	0.48	23.04	2200	1.50	53.8	14.7	0.57	35.0
SP143B12H-42DL	B	12	7.0~13.2	1.75	21.00	2800	1.83	65.0	33.0	1.30	42.0
SP143B24H-42DL	B	24	14.0~26.4	1.15	27.60	2800	1.83	65.0	33.0	1.30	42.0
SP143B48H-42DL	B	48	28.0~56.0	0.55	26.40	2800	1.83	65.0	33.0	1.30	42.0

\*Bearing system B: Two Ball Bearing S: Sleeve Bearing

